

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538



York 300x3x20mm C24RBF FLAT CUTTING DISC

Grade A30 - For general-purpose use on metals. Grade C24 - For use on stone and non-ferrous materials. Grade R30 - For use on stainless steel. Grade X24 - Special, for use on cast iron. Type 41 Flat Reinforced Cutting Manufactured to assure operator safety and optimum performance. For use with all portable angle grinders. 180mm to 230mm discs can also be used on circular saws and 300 to 350mm discs are for use with chop saws/cut-off machines, subject to bore compatibility. Not to be used for wet cutting.

SKU Optimum Angle For Use 90 Ű Bore 20 Hardness Hard Additional Conformity Manufactured According to EN12413 Thickness 3 mm Series Stone Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For Use On Non Ferrous Metal Grade Designation	Specifications	Details
Bore 20 Hardness Hard Additional Conformity Manufactured According to EN12413 Thickness 3 mm Series Stone Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	SKU	YRK2309090GTSK
Hardness Hard Additional Conformity Manufactured According to EN12413 Thickness 3 mm Series Stone Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Optimum Angle For Use	90 °
HardnessHardAdditional ConformityManufactured According to EN12413Thickness3 mmSeriesStoneGrain Size24-CoarseMaximum RPM5100Cutting ApplicationFor use on Stone and Non Ferrous MaterialsFor Use OnNon Ferrous Metal	Bore	
Thickness 3 mm Series Stone Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Hardness	
Series Stone Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Additional Conformity	Manufactured According to EN12413
Grain Size 24-Coarse Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Thickness	3 mm
Maximum RPM 5100 Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Series	Stone
Cutting Application For use on Stone and Non Ferrous Materials For Use On Non Ferrous Metal	Grain Size	24-Coarse
For Use On Non Ferrous Metal	Maximum RPM	5100
	Cutting Application	For use on Stone and Non Ferrous Materials
Grade Designation C24RBF	For Use On	Non Ferrous Metal
	Grade Designation	C24RBF
Type Type 41	Туре	Type 41
Special Features Good Performance Competitively Priced	Special Features	Good Performance Competitively Priced
Disc Diameter 300 mm	Disc Diameter	300 mm
Bond Type Resin Bonded with Fibre Reinforcment	Bond Type	Resin Bonded with Fibre Reinforcment

E-Mail:gentech@eim.ae Website:www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel:+966 (0) 3 834 4264

Fax: +966 3 834 4538

Specifications	Details	
Weight	1	
Abrasive Material	Silicon Carbide	
Brand	York	

P.O Box 25898 Sharjah United Arab Emirates E-Mail:gentech@eim.ae Phone : 06-5436933/06-5436733 Website: www.generaltech.ae Fax : 06-5437077