



## Chicago Pneumatic CP6763 3/4 Impact Wrenches 350-1290NM

Compact, Robust & Powerful 3/4 impact for industrial maintenance applications. Compact and Versatile for Industrial Maintenance applications. Very hard hitting twin hammer clutch. Robust for the roughest environments and the toughest applications. Range: 350 - 1290 Nm 260 - 950 ft.lbs

| Specifications            | Details                                     |
|---------------------------|---------------------------------------------|
| Square Drive              | 3/4"                                        |
| Model Number              | CP6763                                      |
| Side to center            | Metric: Side to center Imperial: 1.6"       |
| Free Speed                | 6300 rpm                                    |
| Min. Hose Size            | Metric: 13 mm Imperial: 1/2"                |
| Product Number            | 6151590400                                  |
| Length                    | Metric: 222 mm Imperial: 8.74"              |
| Power/weight ratio        | Metric: 296.4 Nm/kg Imperial: 99.2 ft.lb/lb |
| Air inlet thread size     | 3/8"                                        |
| Vibration uncertainty (K) | 1.3 m/s <sup>2</sup>                        |
| Actual air consumption    | Metric: 14.2 l/s Imperial: 30 cfm           |
| Sound pressure            | 96 db(A)                                    |
| Sound Power               | 107 db(A)                                   |
| Range Metric              | 260 - 950 ft.lbs                            |
| Bolt Size                 | M27 mm                                      |
| Net weight                | Metric: 5 1/2 kg Imperial: 12.1 lb          |

| Specifications           | Details                               |
|--------------------------|---------------------------------------|
| Maximum Torque (reverse) | Metric: 1630 Nm Imperial: 1200 ft.lbs |
| Brand                    | Chicago Pneumatic                     |

