



Chicago Pneumatic CP9561 3/4 Impact Wrenches 200-950NM

The industrial grade of the Classic. Industrial Maintenance & Production applications. High performances, especially on hard joints. Operator comfort due to low vibrations and noise level. Great control with a multi-position regulator. Reliable pin clutch in oil bath & durable housing. Compact 3-part construction & easy to maintain. Range: 200 - 950 Nm 150 - 700 ft.lbs

| Specifications | Details |
|---------------------------|---|
| Vibration uncertainty (K) | 2.4 m/s ² |
| Vibration | 7.7 m/s ² |
| Maximum Torque (reverse) | Metric: 1250 Nm Imperial: 885 ft.lbs |
| Range Imperial | 150 - 700 ft.lbs |
| Net weight | Metric: 5.1 kg Imperial: 11.1 lb |
| Power/weight ratio | Metric: 245.1 Nm/kg Imperial: 79.7 ft.lb/lb |
| Actual air consumption | Metric: 14.1 l/s Imperial: 30 cfm |
| Sound pressure | 100 db(A) |
| Side to center | Metric: 39 mm Imperial: 1.54" |
| Free Speed | 5500 rpm |
| Product Number | 6151909561 |
| Brand | Chicago Pneumatic |
| Square Drive | 3/4" |
| Model Number | CP9561 |
| Sound Power | 111 db(A) |
| Air inlet thread size | 3/8" |

| Specifications | Details |
|----------------------------|---|
| Working Torque Range (fwd) | Metric: 200 - 950 Nm Imperial: 150 - 700 ft.lbs |
| Range Metric | 200 - 950 Nm |

