



## Chicago Pneumatic CP2141 Screwdrivers - Impact (Double Rocking Dog) 10-24NM

Compact, fast & easy to use. Compact & Lightweight. Low noise level for operator comfort. Excellent for various MRO applications. Range: 10 - 24 Nm 7.38 - 17.7 ft.lbs

| Specifications         | Details                                       |
|------------------------|---|
| Screw type soft        | x   |
| Screw type hard        | x   |
| Max working torque     | Metric: 24 Nm Imperial: 17.7 ft.lbs           |
| Net weight             | Metric: 0.87 kg Imperial: 1.91629955947137 lb |
| Bit holder             | Hexagonal Female                              |
| Free Speed             | 13000 rpm                                     |
| Min. Hose Size         | Metric: 10 mm Imperial: 3/8"                  |
| Handle Type            | Pistol  |
| Diameter               | Metric: 21 mm Imperial: 0.825"                |
| Length                 | Metric: 143 mm Imperial: 5.62992125984252"    |
| Model Number           | CP2141  |
| Output drive           | 1/4"  |
| Actual air consumption | Metric: 6.23 l/s Imperial: 13.2 cfm           |
| Sound pressure         | 77 db(A)                                      |
| Clutch type            | Impact (Double Rocking Dog)                   |
| Min working torque     | Metric: 10 Nm Imperial: 7.38 ft.lbs           |

| Specifications             | Details   |
|----------------------------|---|
| Height                     | Metric: 150 mm Imperial: 5.90551181102362"        |
| Sound Power                | 88 db(A)  |
| Air inlet thread size      | 1/4"  |
| Brand                      | Chicago Pneumatic                                 |
| Product Number             | 8941021410  |
| Vibration                  | 5.3 m/s <sup>2</sup>                              |
| Vibration ISO              | ISO-28927-2                                       |
| Vibration uncertainty (K)  | 2.1 m/s <sup>2</sup>                              |
| Screw type very soft       | x   |
| Over carton                | Metric: 412*367*212 mm Imperial: 16.22*14.45*8.35 |
| Bolt Size                  | M4-M6 mm  |
| Free speed air consumption | Metric: 8.53 l/s Imperial: 18.07 cfm              |

