



Chicago Pneumatic CP780 Screwdrivers - Cushion 2.83-4.97NM

High speed & Robust. Fast Screws fastening for better productivity. Reliable & easy-to-adjust cushion Clutch. Ideal tool for general repair, wood, PVC & refurbishing applications. Range: 2.83 - 4.97 Nm 2.06 - 3.7 ft.lbs

| Specifications | Details |
|----------------------------|---|
| Handle Type | Pistol |
| Vibration | 2.9 m/s ² |
| Vibration uncertainty (K) | 1.4 m/s ² |
| Sound Power | 109.3 db(A) |
| Average air consumption | Metric: 1.9 l/s 113 l/mn Imperial: 4 cfm |
| Model Number | CP780 |
| Height | Metric: 150 mm Imperial: 5.9" |
| Actual air consumption | Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm |
| Length | Metric: 210 mm Imperial: 8.25" |
| Product Number | T025095 |
| Brand | Chicago Pneumatic |
| Max working torque | Metric: 4.97 Nm Imperial: 3.7 ft.lbs |
| Diameter | Metric: 31 mm Imperial: 0.78" |
| Air inlet thread size | 1/4" |
| Free speed air consumption | Metric: 11.6 l/s Imperial: 25 cfm |
| Net weight | Metric: 1.13 kg Imperial: 2 1/2 lb |

| Specifications | Details |
|--------------------|---------------------------------------|
| Vibration ISO | ISO-28927-2 |
| Min working torque | Metric: 2.83 Nm Imperial: 2.06 ft.lbs |
| Sound pressure | 98.3 db(A) |
| Clutch type | Cushion |
| Bit holder | Quick Change Hexagonal Female |
| Output drive | 1/4" |
| Free Speed | 1800 rpm |
| Min. Hose Size | Metric: 10 mm Imperial: 3/8" |

