



Chicago Pneumatic CP2780 Screwdrivers - Positive 10NM

Compact & High Speed Positive clutch. Perfectly designed for wood applications. Operator can control clutch engagement for higher torque. Convenient one-handed reverse. Good for prevailing torque applications Range: 10 Nm

Specifications	Details
Average air consumption	Metric: 1.2 l/s 71 l/mn Imperial: 2 1/2 cfm
Actual air consumption	Metric: 4.7 l/s 283 l/mn Imperial: 10 cfm
Vibration ISO	ISO-28927-2
Bit holder	Quick Change Hexagonal Female
Product Number	6151922780
Brand	Chicago Pneumatic
Model Number	CP2780
Output drive	1/4"
Max working torque	Metric: 10 Nm Imperial: 7.4 ft.lbs
Net weight	Metric: 1.06 kg Imperial: 2.35 lb
Height	Metric: 149 mm Imperial: 5.9"
Sound Power	100 db(A)
Clutch type	Positive
Free Speed	2100 rpm
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Diameter	Metric: 21 mm Imperial: 0.83"
Air inlet thread size	1/4"
Free speed air consumption	Metric: 14 l/s Imperial: 29.7 cfm

Specifications	Details
Sound pressure	89 db(A)
Vibration uncertainty (K)	- m/s ²
Vibration	
Handle Type	Pistol
Length	Metric: 164 mm Imperial: 6.46"

