



Chicago Pneumatic CP2012 Screwdrivers - Shut off 2-5 1/2NM

Productivity improved. Ideal for multiple applications. Fast cycle times for productivity. Ideal for centering screws during the fastening cycle. Range: 2 - 5 1/2 Nm 1.475 - 4.056 ft.lbs

Specifications	Details
Model Number	CP2012
Output drive	1/4"
Sound pressure	73 db(A)
Clutch type	Shut off
Min working torque	Metric: 2 Nm Imperial: 1.475 ft.lbs
Bit holder	Quick Change Hexagonal Female
Vibration uncertainty (K)	- m/s ²
Screw type soft	x
Screw type hard	x
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Handle Type	Straight
Product Number	6151922012
Diameter	Metric: 34 mm Imperial: 1.33"
Free speed air consumption	Metric: 9 l/s Imperial: 19.1 cfm
Net weight	Metric: 0.9 kg Imperial: 2 lb
Max working torque	Metric: 5 1/2 Nm Imperial: 4.056 ft.lbs
Free Speed	1470 rpm
Air inlet thread size	1/4"
Length	Metric: 278 mm Imperial: 10.9"

Specifications	Details
Brand	Chicago Pneumatic
Vibration ISO	ISO-28927-2

