

## Chicago Pneumatic CP2621 Screwdrivers - Shut off 0.8-6.5NM



Easy high Torque setting for various accurate types of assembly. Ideal for moderate to intensive assembly line. Versatile thanks to wide & high torque. Low Noise for operator comfort. Excellent accuracy for various applications. Range: 0.8 - 6.5 NM 0.59 - 4.79 ft.lbs

Specifications	Details
Vibration uncertainty (K)	- m/s <sup>2</sup>
Bit holder	Quick Change Hexagonal Female
Screw type soft	x
Sound pressure	76 db(A)
Clutch type	Shut off
Min working torque	Metric: 0.8 Nm Imperial: 0.59 ft.lbs
Brand	Chicago Pneumatic
Model Number	CP2621
Output drive	1/4"
Length	Metric: 232 mm Imperial: 9.1"
Screw type hard	x
Max working torque	Metric: 6.5 Nm Imperial: 4.79 ft.lbs
Vibration	<2.5 m/s <sup>2</sup>
Screw type very soft	x
Net weight	Metric: 0.8 kg Imperial: 1.76 lb
Free speed air consumption	Metric: 14.6 l/s Imperial: 30.9 cfm
Air inlet thread size	1/4"
Sound Power	87 db(A)

Specifications	Details
Vibration ISO	ISO-28927-2
Handle Type	Straight
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Free Speed	1000 rpm
Diameter	Metric: 42 mm Imperial: 1.65"
Product Number	6151922621

