



Kern FFN 5IPN 25Kg Bench Scale

Your support in a HACCP-compliant quality system
High mobility: thanks to battery operation, compact construction and low weight, it is suitable for use in several locations such as production, kitchen, sales office etc. Stainless steel housing, rust-proof and easy to clean

| Specifications | Details |
|---------------------------------------|--|
| Minimum humidity | 25 % |
| Tare range: | -25000000 mg |
| Operating time (Backlight on): | 30 h |
| Mains adapter/adapter included: | <input type="checkbox"/> CH EURO UK US |
| Resolution | 5000 |
| Brand | Kern |
| Dimensions housing (WxDxH): | 230 mm x 300 mm x 130 mm |
| Material weighing plate: | stainless steel |
| Weighing surface (WxD): | 237 mm x 197 mm |
| Display digit height: | 25 mm |
| Charging time | 12 h |
| Input voltage | 110 V - 230 V AC |
| Revolving screw feet: | yes |
| Overall dimensions mounted (WÃDÃH): | 230 mm x 300 mm x 130 mm |
| Level indicator: | yes |
| Net weight | 3.82 kgs |
| Gross weight | 4.65 kgs |

| Specifications | Details |
|--------------------------------|----------------------|
| Adjustment options | External calibration |
| Operating time (Backlight off) | 50 h |
| Linearity | 10 g |
| Readout [d] | 5 g |
| Recommended adjusting weight | 25 kg (M3) |
| Reproducibility | 5 g |
| Stabilisation time | 2 s |
| Warm up time | 10 min |
| Weighing range [Max] | 25 kg |
| Weighing system | Strain gauge |
| Weighing units | kg lb |
| Maximum humidity | 95 % |
| Maximum operating temperature | 40 Â°C |
| Minimum ambient temperature | 0 Â°C |