

UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

## Kern FKT 10LM 60kg Bench scale

80 memories for each operation mode, e.g., for checkweighing, PRE-TARE, reference weight, target weight when dispensing etc.Convenient recipe weighing: 99 recipes each with 10 components each can be stored in plain text. If one recipe ingredient is overweight, then the practical recipe adjustment function for when dosages are exceeded automatically calculates the new target weights of the other ingredients. The actual and target values and the proportionate percentage can then be printed. The recipes can be generated easily in an Excel list at the PC and transferred to the balance using the RS-232 interface. Alternatively, the recipes can also be entered directly using the keypadMultiplier function: recipes where the ingredients have been recorded as percentages can easily be multiplied when entering the new target weight is entered, target weight, which is ideal for the production of larger containers, bulk packs etc.Rapid function for shortened stabilisation time with reduced readout16 print forms which can store up to 20 different information, such as, e.g., date, time, operator, item, net, tare, gross, PCS, target weight, PRE-TARE etc. The print forms can be generated easily in an Excel list in the PC and transferred to the balance using the RS-232 interfaceControl outputs (optocoupler, digital I/O) to connect relays, signal lamps, valves etc. (35 V / 80 mA)Hook for underfloor weighing of hanging loads standard for models with weighing plate size For particularly high counting accuracy, there is an option of combining the KERN FKT range with a high-precision reference balance to make a counting system, please enquireModes Weighing Counting Dispensing Recipe weighing Checkweighing Totalising with daily total Percentage determination Animal weighing Surface weight Density determination, only with, not for Rapid function, not for



Specifications	Details
Material weighing plate:	stainless steel
Weighing surface (WxD):	340 mm x 240 mm
Dimensions housing (WxDxH):	350 mm x 390 mm x 120 mm
Model Number	FKT 10LM
Brand	Kern
Product Number	FKT 60K 10LM
Display digit height:	4 mm
Charging time	10 h
Input voltage	100 V - 240 V
Operating time (Backlight off)	20 h
Revolving screw feet:	yes

## ×



UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

Level indicationyesNarwightSafageGross weightNa KageGross weightNa KageMinium ambient temperatureNa KageMainum ange attemperatureNa KageMaximum auditySafageKaighing angeSafageWeighing ange (Max)SafageMarging (Max)SafageSafageSafageSafageSafageSafageSafageResolutionSafageResolutionSafage<	Specifications	Details
Gross weight   7.6 kgs     Minimum ambient temperature   10 ŰC     Maximun operating temperature   80 %     Maximum hunidity   80 %     Weighing units   gkg     Weighing system   60 kg     Weighing system   30 min     Yarm up time   30 min     Stabilisation time   30 s     Reproducibility   600     Reproducibility   5 g     Readout [d]   10 g     Linearity   5 g     Adius adapter/adapter included:   10 h     Yolghing with tolerance range:   9k     Conting function:   9k     Percentage determination   9k	Level indicator:	yes
Minimu anbient temperature10 ŰCMaximu humidity40 ŰCMaximu humidity80 %Velghing units9kgWeighing system9kgWeighing ange [Max]6 kgWeighing ange [Max]30 minWarm up time30 minStabilisation time30 minResolution6 000Resolution5 gResolution5 kgReadout [d]9kgLinearity5 kgAigastenderdengies6 kgMing and perform6 kgMing and perform	Net weight	6.37 kgs
Maximum operating temperature40 ŰCMaximum humidity80%Weighing unitsg kgWeighing system9 kgWeighing ange [Max]60 kgWarm up time30 minStabilisation time300Resolution600Reporducibility5 gRecommended adjusting weight0 kg (22): 10 kg (22)Readout [d]10 gLinearity5 gAdjustment options5 gMains adapter/adapter included:01 hVeighing with tolerance range:9 kgCounting function:9 kgParenal (d)9 kgWeighing weight0 kgMains adapter/adapter included:0 kgMains adapter/adapter included:9 kgCounting function:9 kgMains adapter/adapter included:9 kgMains adapter included:9 kgMains adapter included:9 kg<	Gross weight	7.6 kgs
Naximum humidity80%Maximum humidity9 kgWeighing units9 kgWeighing system60 kgWeighing range [Max]60 kgWarn up time3 sStabilisation time6000Reproducibility6 000Reproducibility5 gRecommended adjusting weight5 lg (E2); 10 kg (E2)Readout [d]10 gLinearity5 gAdjustment options5 gMains adapter/adapter included:0 hOperating filme (Backlight on):10 hWeighing with tolerance range:9 seCounting function:9 seCounting function:9 sePreventing time (Backlight on):9 seCounting function:9 sePreventing time (Backlight on):9 seCounting function:9 sePreventing time (Backlight on):9 seCounting function:9 seCounting functio	Minimum ambient temperature	10 °C
Weighing unitsg kgWeighing systemStain gaugeWeighing systemG0 kgWeighing range [Max]S on inWarn up timeS on inStabilisation timeG000ResolutionS on inResolutionS on inRenomended adjusting weightS on (Sec 2000)InearityS on (Sec 2000)Adjustment optionsS on (Sec 2000)Operating time [BackRight on ):S on (Sec 2000)Veighing with tolerance range:S on (Sec 2000)Counting function:Son (Sec 2000)Counting function: <td< td=""><td>Maximum operating temperature</td><td>40 °C</td></td<>	Maximum operating temperature	40 °C
Neighing systemStrain agueWeighing range [Max]60 kgWeighing range [Max]3 minStabilisation time3 sStabilisation time6000Resolution6000Reproducibility5 gRecommended adjusting weight0 kg (E2): 10 kg (E2): 10 kg (E2)Readout [d]10 gLinearity5 gAdjustmen options6 kg (E2): 10 kg (E2)Nins adapter/adapter included:CH EUROVeighing with tolerance range:9 kgVeighing with tolerance range:6 kgCounting function:9 kgRender determination10 kgStore add termination10 kgSto	Maximum humidity	80 %
Weighing range [Max]60 kgWarm up time30 minStabilisation time3 sResolution6000Reproducibility5 gRecommended adjusting weight0 kg (E2): 10 kg (E2)Readout [d]10 gLinearity5 gAdjustment options5 gMains adapter/adapter included:CH EUROOperating time (Backlight on):0 hVielighing with tolerance range:60 kgCounting function:yesPercentage determinationyesCounting resolution:yesCounting resolution:yesCou	Weighing units	g kg
Name30 minStabilisation time3 sResolution6000Report of time5 gRecommended adjusting weight0 s0 (s20 (s20 (s20 (s20 (s20 (s20 (s20	Weighing system	Strain gauge
Stabilisation time3 sResolution6000Reproducibility5 gRecommended adjusting weight0 log (22); 10 kg (22)Readout [d]10 gLinearity5 gAdjustment options5 gAdjustment optionsCH EUROOperating time (Backlight on):10 hVieighing with tolerance:9 sTare range:60 kgCounting function:9 sPercentage determination9 sCounting runcion:9 sCounting runci	Weighing range [Max]	60 kg
Aesolution6000Reproducibility5 gRecommended adjusting weight0 log (202)Readout [d]0 gInearity5 gAdjustment options5 gAdjustment options0 HEUROOperating time (Backlight on):0 HEUROVeighing with tolerange:0 sgTare range:6 logArean end end end end9 sgPercentage determination9 sgCounting function:9 sgAutor options9 sgAutor options <td>Warm up time</td> <td>30 min</td>	Warm up time	30 min
ReproducibilitySRecommended adjusting weightSReadout [d]O g (22); 10 kg (22)Readout [d]SLinearitySAdjustment optionsSAdjustment optionsMine CalibrationNerrange:O hVeighing with tolerance range:SoCounting function:SoPercentage determinationSoCounting resolutionSoCounting resolutionSoS	Stabilisation time	3 s
InterpretationInterpretationRecommended adjusting weight50 kg (E2); 10 kg (E2)Readout [d]10 gLinearity5 gAdjustment optionsExternal calibrationMains adapter/adapter included:CH EUROOperating time (Backlight on):10 hVeighing with tolerance range:gesTare range:60 kgCounting function:yesPercentage determinationgesCounting resolution6000	Resolution	6000
Readout [d]10 gLinearity5 gAdjustment optionsExternal calibrationMains adapter/adapter included:CH EUROOperating time (Backlight on):10 hWeighing with tolerance range:yesTare range:00 kgCounting function:yesPrecentage determinationyesCounting resolution6000	Reproducibility	5 g
Linearity5 gAdjustment optionsExternal calibrationMains adapter/adapter included:CH EUROOperating time (Backlight on):JohVeighing with tolerance:ysaTare range:Gol kgCounting function:ysaPrecentage determinationysaCounting resolutiononoHerting time optionsysaCounting resolutiononoHerting time optionsonoHerting time optionsonoCounting resolutiononoHerting time optionsonoHerting time optionsonoHert	Recommended adjusting weight	50 kg (E2); 10 kg (E2)
Adjustment optionsExternal calibrationMains adapter/adapter included:CH EUROOperating time (Backlight on):10 hWeighing with tolerance range:yesTare range:60 kgCounting function:yesPercentage determinationyesCounting resolution6000	Readout [d]	10 g
Nains adapter/adapter included:CH EUROOperating time (Backlight on):10 hWeighing with tolerance range:yesTare range:60 kgCounting function:yesPercentage determinationyesCounting resolution6000	Linearity	5 g
Operating time (Backlight on):10 hWeighing with tolerance range:yesTare range:60 kgCounting function:yesPercentage determinationyesCounting resolution6000	Adjustment options	External calibration
Weighing with tolerance range:yesTare range:60 kgCounting function:yesPercentage determinationyesCounting resolution6000	Mains adapter/adapter included:	CH EURO
Tare range:60 kgCounting function:yesPercentage determinationyesCounting resolution6000	Operating time (Backlight on):	10 h
Counting function:yesPercentage determinationyesCounting resolution6000	Weighing with tolerance range:	yes
Percentage determination yes   Counting resolution 6000	Tare range:	60 kg
Counting resolution 6000	Counting function:	yes
	Percentage determination	yes
Mininum piece weight at piece counting (Laboratory 10 g	Counting resolution	6000
	Mininum piece weight at piece counting (Laboratory	10 g



UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

Specifications	Details
Mininum piece weight at piece counting (Normal)	100 g
Function to save totals:	yes
PRE-TARE function:	yes
Standby function:	yes
Time display:	yes
Suspended weighing	Hook
Reference weight:	yes
Conversion function:	yes
Dispensing function:	yes
SLEEP function:	yes
Statistical function:	yes
Vibration-free weighing (Animal weighing program)	yes