

UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538



Norbar HT2/25 AWUR 3/4 Manual Torque Multipliers 170-1700NM, Output Square: 3/4", Input Square: 1/2"

Multiple stages of epicyclic gearing are used in Norbar's 'HandTorque' multipliers to provide a wide range of torque outputs and ratios to suit most applications. The torque multiplication ratio is always quoted, not the velocity ratio as some competitors' goods claim. For example, a velocity ratio of 29.8:1 would result in a torque multiplication of 25:14%.

Specifications	Details
Plate Torque	9 N.m
Model Number	HT2/25 AWUR 3/4"
Accuracy	+/-4%
Product Number	16088
Brand	Norbar
Max Input Speed	210 revs/min
Tool Weight	5.5 Kg
Range Metric	170.0 - 1700.0 N·m
Range Imperial	125.0 - 1250.0 lbf·ft
Plate Weight	2.2 Kg
Velocity Ratio	29.752:1
Input Square	1/2"
Output Square	3/4"
Multiplication Ratio	25:1