

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

Norbar HT5/75 1 Manual Torque Multipliers 340-3400NM, Output Square: 1", Input Square: 1/2"



Multiple stages of epicyclic gearing are used in Norbar's 'HandTorque' multipliers to provide a wide range of torque outputs and ratios to suit most applications. The torque multiplication ratio is always quoted, not the velocity ratio as some competitors' goods claim. For example, a velocity ratio of 29.8:1 would result in a torque multiplication of 25:14%.

Specifications	Details
Plate Torque	19 N.m
Max Input Speed	315 revs/min
Tool Weight	7.9 Kg
Accuracy	+/-4%
Product Number	16064.75
Range Metric	340 - 3400 N·m
Range Imperial	250 - 2500 lbf·ft
Plate Weight	2.5 Kg
Velocity Ratio	93.137:1
Input Square	1/2"
Output Square	1"
Multiplication Ratio	75:1
Model Number	HT5/75 1"
Brand	Norbar

P.O Box 25898 Sharjah Phone : 06-5436933/06-5436733 E-Mail : gentech@eim.ae United Arab Emirates Fax : 06-5437077 Website : www.generaltech.ae