

UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538



Pi tape 0.01mm Graduation, 300 - 600 mm Measurement, Spring Steel Diameter Tape Measure

Pi Tape® brand Precision Diameter tapes are manufactured to exacting standards in temperature controlled facilities at $68\tilde{A}^{-}\hat{A}\dot{c}\hat{A}^{1/2}F$ ($20\tilde{A}^{-}\hat{A}\dot{c}\hat{A}^{1/2}C$). The lines and numerals on our standard tapes are engraved and acid etched on a ground surface. The tapes have fixed readings that do not require periodic adjustments. Standard tapes have an accuracy of $\tilde{A}^{-}\hat{A}\dot{c}\hat{A}^{1/2}$.001" up to 144 $\tilde{A}^{-}\hat{A}\dot{c}\hat{A}^{1/2}$ ($\tilde{A}^{-}\hat{A}\dot{c}\hat{A}^{1/2}$.03mm up to 3600mm)

Specifications	Details
Thickness	0.15 mm
Graduations	0.01 mm
Brand	× Pi Tape
Material	Spring Steel
Width	12.7 mm
Maximum measurement (mm/inch)	600 mm
Minimum Measurement (mm/inch)	300 mm