

UAE Email:mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

Yamoto 10 SATIN-CHROME ADJUSTABLE WRENCH

Slimline tapered parallel jaws for improved access into confined spaces with smooth jaw adjustment and selflocking design prevents the jaws opening unintentionally even when under full load. Graduated laser etched jaws for fast repeatable jaw setting and adjustment. Manufactured from â[][Iâ]]] beam section chrome vanadium steel for improved strength and rigidity, he jaws are heat treated for extended tool life. Corrosion-resistant satin finish. 22.5Ű offset head angle for positive torque control.Suitable for marine engineering, automotive, aerospace, agricultural maintenance and assembly applications. Conform to: ISO 6787-1982, ASME B.107.8M-1996, BS 6333-199405, DIN3117-1988, JIS B4604-1976. Torque Ratings Conform to ISO 6787:1982.

Specifications	Details
SKU	YMT5012100GTSK
Туре	Adjustable Wrench
Special Features	Corrosion-resistant Graduated Scale Heat treated jaws
Overall Length	250 mm
Number Of Pieces	1
Standards Met	ASME B.107.8M-1996 BS 6333-199405 DIN3117-1988 ISO 6787-1982 ISO 6787:1982 JIS B4604-1976
Handle Material	Steel
Jaw Material	Steel
Finish/Coating	Satin
Maximum Jaw Capacity	30 mm
Head Angle	22.5 °
Brand	Yamoto

