

Technical Data

Battery: SR44 (1 pc), 938882

Optional Accessories

Code No.	Description
264-622	U-WAVE-TM transmitter
02AZF310	U-WAVE-TM connection unit
05CZA662	SPC data cable with pushbutton (1 m)
05CZA663	SPC data cable with pushbutton (2 m)
06AFM380B	USB input tool direct USB-ITN-B (2 m)



SERIES 342 – Digimatic Point Micrometer

- Pointed spindle and anvil for measuring the web thickness of drills, small grooves, keyways, and other hard-to-reach features.
- The measuring points (carbide tipped) have, approximately, a 0.3 mm radius.
- Equipped with Ratchet Stop for constant measuring force.

MeasurLink[®] ENABLED
Data Management Software by Mitutoyo

IP65



342-351-30

B

Specifications

Inch/Metric

Code No.	Range	Resolution	Accuracy*	Point
342-351-30	0-1" (0-25.4 mm)	.00005" (0.001 mm)	±.0001" (±2 μm)	15°
342-352-30	1-2" (25.4-50.8 mm)			
342-353-30	2-3" (50.8-76.2 mm)			
342-354-30	3-4" (76.2-101.6 mm)		±.00015" (±3 μm)	30°
342-361-30	0-1" (0-25.4 mm)			
342-362-30	1-2" (25.4-50.8 mm)		±.0001" (±2 μm)	
342-363-30	2-3" (50.8-76.2 mm)	±.00015" (±3 μm)		
342-364-30	3-4" (76.2-101.6 mm)			

* Excluding quantizing error.

Dimensions

