


**EVC015**

VDOAH040MSS00.3H04STGH040MSS

Connection technology



**Product characteristics**

Jumper

M12 plug / M12 socket

Free from silicone

Free from halogen

Gold-plated contacts

**Electrical data**

Electrical design		AC/DC
Operating voltage	[V]	250 AC / 300 DC
Current rating	[A]	4
Protection class		II

**Environment**

Ambient temperature	[°C]	-25...90, cRUUs: max. 75 °C
Ambient temperature (moving)	[°C]	-25...90, cRUUs: max. 75 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

**Mechanical data**

Design		straight / angled
Material body		housing: TPU orange; sealing: Viton
Material nut		Brass; nickel-plated
Tightening torque for knurled nut [Nm]		plug: 0.6...1.5 *) / socket: 0.6...1.5
Drag chain suitability		<p>Bending radius for flexible applications:</p> <p>min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s<sup>2</sup></p> <p>Travel speed: 5 m/s<sup>2</sup></p> <p>Bending cycles: &gt; 5 million</p> <p>Torsional strain: ± 180 °/m</p>
Weight	[kg]	0.044

**Electrical connection**

Connection		PUR cable / 0.3 m; 4 x 0.34 mm <sup>2</sup> (42 x Ø 0.1 mm); Ø 4.9 mm; halogen-free
Sheath colour		black



**Wiring**



## EVC015

VDOAH040MSS00.3H04STGH040MSS

Connection technology



### Remarks

Remarks

\*) Take into account the maximum value of the counterpart!

Pack quantity

[piece]

1