



PNEUTORQUE® PTME-72 SERIES



Designed to meet the needs of the commercial vehicle market, the integrated reaction foot of the PTME-72 series of tools reaches recessed wheel bolts whilst the 72 mm diameter gearbox handles the high frequency of use demanded by busy tyre shops.

- IC and EC tools have an accuracy of ±2%



11	PTME-72 SERIES - STALL TOOLS - BI-DIRECTIONAL*	£
18140.B06	¾" sq. dr., 200 - 1,000 N·m, 147 - 738 lbf-ft	
18149.B08	1" sq. dr., 200 - 1,000 N·m, 147 - 738 lbf-ft	
18141.B08	1" sq. dr., 400 - 2,000 N·m, 295 - 1,475 lbf-ft	

*Comes supplied in a carry case.

Stall tools are also available as forward only tools, replace B with F when ordering. Deduct £306.60 from above prices.

11	PTME-72 SERIES - SHUT-OFF TOOLS - BI-DIRECTIONAL - INTERNAL	£
18142.B06	¾" sq. dr., 200 - 1,000 N·m, 147 - 738 lbf-ft (IC)	
18143.B08	1" sq. dr., 400 - 2,000 N·m, 295 - 1,475 lbf-ft (IC)	

11	PTME-72 SERIES - SHUT-OFF TOOLS - BI-DIRECTIONAL - EXTERNAL (Requires Tool Controller, see page 111)	£
18144.B06	¾" sq. dr., 200 - 1,000 N·m, 147 - 738 lbf-ft (EC)	
18145.B08	1" sq. dr., 400 - 2,000 N·m, 295 - 1,475 lbf-ft (EC)	

Model	PTME-72-1000-B	PTME-72-2000-B
Part Number	18140.B06 18149.B08	18141.B08
Output Speed (rpm)	122	58
Dimensions (mm)	ØD max.	72
	H1	29
	H2	224
	H3	116
	L	403
	R1	81
	R2 min.	63
	R2 max.	110
Tool Weight (kg)	7.2	7.7

