

Features

- Shore "A" hardness tester designed to measure hardness of rubber, elastomers, natural rubber products, neoprene, polyester, resin, leather and soft PVC
- Meets DIN 53505, ASTM D2240, ISO 7619 and JISK 7215
- 4-digit, LCD display
- Pocket-sized model with integrated probe
- Maximum and Average functions
- Zero adjustment button
- Low battery indicator and auto shut off
- Includes wrist strap, test block, batteries and hard carrying case

Specifications

Measuring Range:	10 to 90 HA
Deviation:	±1 HA
Resolution:	0.1 HA
Sampling Time:	1 sec.
Display:	4-digit, LCD
Zero Button:	Yes
Max and Average Functions:	Yes
Power Supply:	2 AAA Batteries
Low Battery Indicator:	Yes
Product Certifications:	CE
Operating Temperature:	32 to 104°F (0 to 40°C)
Storage Temperature:	-4 to 140°F (-20 to 60°C)
Operating Humidity:	20 to 90%
Dimensions:	6.4 x 2.6 x 1.5" (162 x 65 x 38mm)
Weight:	6.1oz (173g)

TECHNICAL DATA



Model	Description
HT-6510A	"A" Scale Durometer
R8888	Deluxe Hard Carrying Case
HT-6510A-NIST	"A" Scale Durometer & NIST